



REVOLUTION Rx



Science Based Protection

FILTR's Revolution Rx was engineered based on how the cleanest FDA regulated environments in the world are designed and maintained for optimum product and people protection from airborne contaminants.

HEPA™

With its HEPA technology, FILTR removes 99.95% of all particles such as mold spores, bacteria and viruses. With filtration down to 0.01 μm you can be assured you are protected from harmful airborne contaminants.

Create a Clean Air Buffer to Protect Patient and Staff

Clean your recovery room, treatment room and isolation room using the cleanroom filter technique. Add more HEPA filtered air to these rooms to reduce particle levels. No upgrade or reconstruction of your air handling system required. Reduced particle level in your room means reduced risk of infection.

FEATURES

- Commercial Grade Air Purification
- Removes Bacteria, Viruses and Microbes
- 5 lbs. Carbon Filter
- Removes Harmful Volatile Organic Compounds (VOC) from the air
- Cleanroom Grade HEPA Filtration down to 0.01 micron
- Duct Air In or Out to Positively or Negatively Pressurize a Room
- Onboard Sensors provide Real Time Environmental Data Status for PM 2.5, VOC, Temperature and Humidity





TECHNICAL DATA SHEET

FILTR DETECT AND PROTECT

Features

Low Speed	200 CFM (339 m3/h)	
Medium Speed	350 CFM (594 m3/h)	
High Speed	500 CFM (849 m3/h)	700 CFM (1189 m3/h) without Carbon Filter
Filtration	Pre Filter, Filtration Carbon Filter (5 lbs.), HEPA (98 sqft media)	
EN 1822 classification for HEPA	HEPA Class H13	
HEPA Efficiency	99.95% at 0.2µm (MPPS)	
Coverage Area	12,000 cubic feet	
Onboard Sensors	Particle Mass (PM2.5), VOC, Temperature, Humidity	
Housing	White Powder Coated Aluminum	
Control	Local Switch or Remote Via WiFi and Phone App	
Mounting	Floor or optional wall or ceiling mounting available	
Power Requirements	100-130 volts 50/60 Hz/1.7 amps or 200-240 volts 50/60 Hz/0.9 amps	
Weight	39 lbs. (17.7 kg)	
Dimensions	Height 30.5" (77.47 cm), width 15.3" (38.8 cm)	
Operating Temperature/Humidity	50°F to 104°F (10°C to 40°C), 20% to 95% relative humidity, non-condensing	
Warranty	1 Year	

Included: HEPA Filter, Activated Carbon Filter, Pre-Filter, Onboard Sensors (PM 2.5, VOC, Temperature, Humidity), iPhone or Android App downloadable from the Apps Store, 4x wheels, 6 foot power cord.

Optional: Wall Mounting Brackets, Ceiling Mounting Brackets, 10" Inlet Duct Adapter, 10" Outlet Duct Adapter.

DISTRIBUTED BY:



* Patent Pending
Lighthouse Worldwide Solutions reserves the right to change specifications without notice.



grupoalava.com
alava@grupoalava.com
(+34) 91 567 97 00

